

M-Loc™


Commercial and Residential Roof and Wall Panel



An *attractive* and *reliable* all-purpose panel

This versatile panel has long served customers with lasting durability and a pleasing appearance. Its sturdy design provides resistance to the most severe weather and is an excellent choice when the project requires a commercial-strength panel with a low-rib appearance.

- M-Loc is a structural roof and wall panel that can be installed directly over purlins or joists.
- This panel is produced in our Cedar Hill, TX, and Mount Airy, NC, facilities. Longer lead times may apply.




RECOMMENDED 1:12 PITCH AND ABOVE	26 GAUGE	36" OVERALL COVERAGE	13/16" MAXIMUM RIB HEIGHT
--	--------------------	-----------------------------------	--



WWW.CENTRALSTATESMFG.COM

Copyright © 2018, Central States Manufacturing, Inc., All Rights Reserved.
CentralGuard® is a trademark of Central States® Manufacturing, Inc.
Galvalume® is a registered trademark of BIEC International, Inc.

 FLYR_MLOC_180523

Choose CentralGuard[®] for the best protection and a lifetime warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Available on our Prime panels, the CentralGuard name is a guarantee that you have the best protection and a lifetime paint warranty.

Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

	THRIFTY	OUR BEST SELLER! PRIME CentralGuard
FADE PROTECTION		
Paint Warranty	20-YEAR	LIFETIME
Paint Thickness	THIN .70 mil	THICKER 1.0 mil
Fade Warranty	-	30-YEAR
Fade Protection	✓	✓✓
RUST BLOCKING		
Advanced Rust Blocking	-	✓
Perforation Warranty	-	20-YEAR
Substrate Thickness	1.12 mil	1.60 mil
DENT RESISTANCE		
Advanced Dent Resistance	-	✓✓
Steel Thickness	THIN	THICK
Steel Gauge	26 ga.	26 ga.
INSTALLATION		
Purlin Bearing Leg	-	✓



MINIMUM SPECIFICATIONS FOR PRIME PAINTED PANELS

GAUGE

26 ga. | 24 ga.*

STEEL THICKNESS

26 ga. 0.0185" | 24 ga. 0.0230"

PAINT THICKNESS

Top coat paint: .70 mil
Top coat primer: .30 mil
Bottom coat backer: .35 mil
Bottom coat primer: .35 mil

TOTAL THICKNESS

26 ga. 0.0202" | 24 ga. 0.0247"

RUST PROTECTANT SUBSTRATE

Galvalume[®] AZ50

STEEL STRENGTH

80,000 PSI (26 ga.) | 50,000 PSI (24 ga.)

PAINT SYSTEM

SMP

WARRANTY

Lifetime limited paint adhesion
30-yr. chalk and fade
20-yr. Galvalume perforation

TESTING & APPROVALS

APPROVALS

UL2218	UL Approval, Impact Resistance, Class 4
UL580	UL Approval, Uplift Resistance, Class 90
UL790	UL Approval, Fire Resistance, Class A
RC-445	Texas Windstorm Approval, 26 ga. Over Steel Purlins

Find more information at
centralstatesmfg.com

* 24 ga. available in Polar and Galvalume, acrylic-coated bare in select plants